

 <b>thrislington cubicles</b>	
Product: flow glass	Contact: t +44 1244 520 677 w www.thrislingtoncubicles.com e info@thrislingtoncubicles.com
k32 Specification	

## k32 flow glass

### Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,  
Sandycroft, Deeside, Flintshire, CH5 2QZ.  
t: +44 1244 520677 f: +44 1244 535670  
e: info@thrislingtoncubicles.com

**Specification:** Overall cubicle height up to 2700mm with an 8mm floor clearance.

**Framework:** Full anodised aluminium frame, with extruded headrail finished to complement glass colour. Lock locates into receiver integrated within the vertical fascia.

**Door:** 42mm finished thickness consisting of a 29mm ultra lightweight MDF core, faced in high pressure laminate, then rebated and hand-lipped, to accept 5mm low-iron back painted toughened glass to both faces. Concealed fixings within the door allow attachment to stainless steel pivots, suspended from aluminium headrail and located onto floor fixed pivot bracket. Door falls closed by means of a hydraulic door closer concealed within the aluminium headrail (alternatively, the closer can be factory set to fall open).

**Fascia:** 70mm finished thickness consisting of two 12mm moisture resistant MDF core panels, faced in high pressure laminate, then edged all round and attached to a central aluminium frame. Panel faces finished with 5mm low-iron back painted safety glass. Flush aluminium lock receiver fitted into frame.

**Divider:** 37mm finished thickness consisting of a 25mm moisture resistant chipboard core, faced in high pressure laminate and finished to top and bottom edges. Two adjacent 5mm low-iron back painted toughened glass panels, bonded to each face. Suspended 8mm from the floor using concealed fixings (alternatively, the divider can be located in a floor channel).

**Fittings:** Engineered 303 grade brushed stainless steel lock, fixed through the door to the face plate for added strength. Sacrificial hard nylon shear tip to the lock finger, which locates into flush receiver, integrated within the cubicle fascia. Complete with emergency release facility and buffer. Divider fixed to back wall using concealed steel brackets, fastened by hidden through-fixings. Divider connected to front fascia using unique magnetic invisible fixings. Stainless steel coat hook supplied as standard.

### Finishes:

Door: 5mm low-iron toughened glass, back painted colours from our standard range.

Fascia: 5mm low-iron safety glass, back painted colours from our standard range.

Divider: 5mm low-iron toughened glass, back painted colours from our standard range.