



thrislington cubicles

Product: fusion alu

Contact: t +44 1244 520 677

w thrislingtoncubicles.com

n10 Specification

e info@thrislingtoncubicles.com

n10 fusion aluminium lockers

Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,
Sandycroft, Deeside, Flintshire, CH5 2QZ.
t: +44 1244 520677 f: +44 1244 535670
e: info@thrislingtoncubicles.com

Specification: Fully assembled unit with aluminium locker body and aluminium door, supplied in a variety of height, width and depth combinations. Multiple lock options available.

Application: Suitable for use in dry areas and can be situated in a variety of layouts, such as to a back wall, as a free-standing unit, back to back in an island configuration, or fitted into a recess.

Can sit directly on to a pre-installed plinth by others, or a plywood plinth can be provided to suit. The plinth can be finished with a horizontal fascia panel, or alternatively tiling/vinyl by others. Lockers can be fixed to a back wall to give a floating appearance. Integral bench seating can be supplied to supplement the layout.

Configuration: Lockers are supplied in multiple configurations from 1 to 6 tiers and are also available as 2 tier Z lockers.

Standard locker height excluding plinth is 1800mm, but can be supplied from 900mm to 2000mm as required. Lockers are available in a standard width of 300mm and depth of 450mm, complete with injection moulded, chlorine-resistant polypropylene base, top and shelves. Units can be supplied at a bespoke width and depth, by incorporating aluminium base, top and shelves. A vertical fascia panel to allow scribing to a wall or to provide a fitted appearance can be supplied in a matching finish.

Body: 1mm mill finished aluminium sheet body with a radius to the internal corners to reduce dirt traps and pre-drilled holes for site fixing. Continuous spring loaded hinges locate into extruded aluminium profiles. Where layout results in an exposed end, a return panel can be supplied in a finish to match the doors.

Door: 11mm finished thickness, consisting of 9mm plywood core, edged all round in a matching laminate and then faced both sides in sheet aluminium.

Fascia/Return end: Where requested, 11mm finished thickness, consisting of 9mm plywood core, edged all round and then faced both sides in wood veneer.

Fittings: Anodised aluminium studs on the outer face of the door, through-fixed into the continuous hinges for added strength, using stainless steel screws. As a standard, lockers are supplied with either hasp & clasp or cam locks. Alternatives are coin operated, card operated or digital locks. Cam, coin operated and card operated locks are supplied with two keys and a tag, which can be numbered. Flexible PVC straps can be supplied. With the exception of digital locks, an anodised aluminium faceplate is provided, which also can be numbered. All lockers over 900mm high are supplied with a nylon coat hook.

Finishes

Body: 1mm mill finished aluminium.

Door: 1mm satin anodised aluminium sheet.