

 <b>thrislington cubicles</b>	
Product: icon glass	Contact: t +44 1244 520 677 w www.thrislingtoncubicles.com e info@thrislingtoncubicles.com
k32 Specification	

## k32 icon glass

### Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,  
Sandycroft, Deeside, Flintshire, CH5 2QZ.  
t: +44 1244 520677 f: +44 1244 535670  
e: info@thrislingtoncubicles.com

**Specification:** Overall cubicle height up to 2000mm with 150mm floor clearance.

**Framework:** Full anodised aluminium frame, with extruded headrail and vertical posts. Lock locates directly into vertical closing post, incorporating full length buffer.

**Door:** 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Flush aluminium studs secured through the door to the pivot brackets, allow the door to pivot between aluminium headrail and engineered aluminium foot. Foot incorporates height adjustment and sealed bearing providing self-closing mechanism (alternatively, the mechanism can be factory set to fall open). Complete with anti-finger trap clearance on pivot side of door.

**Divider:** 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Supported 150mm from the floor by an engineered anodised aluminium foot, with height adjustment.

**Fascia:** Where required, 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. If a fascia exceeds the width of 150mm, it will need to be supported by an aluminium foot.

**Fittings:** Engineered anodised aluminium lock, fixed through the door to the face plate for added strength. Incorporating a machined aluminium bar, with a sacrificial hard nylon shear tip, which locates into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using through-fixed extruded aluminium brackets. Aluminium coat hook supplied as standard.

### Finishes:

**Door:** 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

**Divider:** 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

**Fascia:** 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.