

 thrislington cubicles	
Product: icon ss	Contact: t +44 1244 520 677 w www.thrislingtoncubicles.com e info@thrislingtoncubicles.com
k32 Specification	

k32 icon stainless steel

Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,
Sandycroft, Deeside, Flintshire, CH5 2QZ.
t: +44 1244 520677 f: +44 1244 535670
e: info@thrislingtoncubicles.com

Specification: Overall cubicle height up to 2000mm with 150mm floor clearance.

Framework: Full anodised aluminium frame, with extruded headrail and vertical posts. Lock locates directly into vertical closing post, incorporating full length buffer.

Door: 27mm finished thickness consisting of a 25mm moisture resistant chipboard core, edged top and bottom in matching high pressure laminate, then faced both sides with stainless steel sheet, each double folded to create vertical seam in the centre of the door edge. Flush aluminium studs secured through the door to the pivot brackets, allow the door to pivot between aluminium headrail and engineered aluminium foot. Foot incorporates height adjustment and sealed bearing providing self-closing mechanism (alternatively, the mechanism can be factory set to fall open). Complete with anti-finger trap clearance on pivot side of door.

Divider: 17mm finished thickness consisting of a 15mm moisture resistant chipboard core, lipped to the back edge in matching high pressure laminate, faced both sides with stainless steel sheet, each folded to create a horizontal seam in the centre of the divider edge. Supported 150mm from the floor by an engineered anodised aluminium foot, with height adjustment.

Fascia: Where required, 17mm finished thickness consisting of a 15mm moisture resistant chipboard core, lip-edged first to visible edges in a matching high pressure laminate, then faced with stainless steel sheet. If a fascia exceeds the width of 150mm, it will need to be supported by an aluminium foot.

Fittings: Engineered anodised aluminium lock, fixed through the door to the face plate for added strength. Incorporating a machined aluminium bar, with a sacrificial hard nylon shear tip, which locates into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using through-fixed extruded aluminium brackets. Aluminium coat hook supplied as standard.

Finishes:

Door: 1mm brushed stainless steel sheet.

Divider: 1mm brushed stainless steel sheet.

Fascia: 1mm brushed stainless steel sheet.