



k32 polo cgl cubicles

Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,
Sandycroft, Deeside, Flintshire, CH5 2QZ.
t: +44 1244 520677 f: +44 1244 535670
e: info@thrislingtoncubicles.com

Specification: Overall cubicle height 2000mm with 150mm floor clearance.

Framework: Full powder coated aluminium frame in specified finish, including extruded aluminium headrail and vertical posts. Lock locates directly into vertical closing post, including buffers.

Door: 12mm compact grade laminate, polished to all edges. Extruded through-fixed aluminium brackets allow the door to pivot between aluminium headrail and floor fixed foot. Foot incorporates a rise and fall closing mechanism and includes height adjustment. Complete with anti-finger trap clearance on pivot side of door.

Divider: 12mm compact grade laminate, polished to all visible edges. Supported 150mm from the floor by a powder coated aluminium foot, with height adjustment.

Fascia: Where required, 12mm compact grade laminate, polished to all visible edges. If a fascia exceeds the width of 150mm, it will need to be supported by an aluminium foot.

Fittings: Painted aluminium lock, fixed through the door to the face plate for added strength. Sacrificial hard nylon shear tip to the lock finger, which locates directly into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using extruded powder coated aluminium brackets secured using through-fixings. Powder coated aluminium coat hook supplied as standard.

Finishes:

Aluminium: Powder coated dark grey (RAL 7011) or light grey (RAL 7035).

Door: 12mm compact grade laminate from our standard range.

Divider: 12mm compact grade laminate from our standard range.

Fascia: 12mm compact grade laminate from our standard range.