

 thrislington cubicles	
Product: sentry veneer	Contact: t +44 1244 520 677 w www.thrislingtoncubicles.com e info@thrislingtoncubicles.com
k32 Specification	

k32 sentry veneer access module

Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,
Sandycroft, Deeside, Flintshire, CH5 2QZ.
t: +44 1244 520677 f: +44 1244 535670
e: info@thrislingtoncubicles.com

Specification: Fully pre-fabricated hinged access panel module up to 3000mm high. Overall depth from the rear of the framework to the front face of panel is 82mm. The system is not designed to prevent water penetration. In a shower situation, we would recommend the use of sentry with compact grade laminate panels.

Application: The system is suitable for use inside toilet cubicles with a WC toilet pan, or as wall lining and can be used to a back wall or in a back to back layout. Although the system will provide some acoustic dampening, it is not designed for that purpose and in a back to back configuration, we would recommend that an acoustic wall is inserted between the two sets of modules.

Can be used with urinals and wash hand basins, but we would recommend that sentry compact grade laminate or sentry glass be considered for these applications. Where a wall-hung WC toilet pan is used, the pan needs to have its own weight-bearing support, supplied by others.

Framework: Full aluminium frame, factory assembled using extruded vertical posts and horizontal cross rails, manufactured to bespoke width and height and supported by zinc-plated mild steel adjustable feet. Frame locates into floor and ceiling channel and is braced to the back wall with aluminium angle, to a specified distance (standard is 300mm to the face of the panels). This framework fully supports the module and no other framework needs to be in place to enable the fitting of the system.

Access Panels: 17mm finished thickness consisting of a 15mm moisture resistant chipboard/MDF core. Panels are edged first and then faced with wood veneer, with balancing backing laminate. The standard configuration allows for 3 panels per module, although this can be varied to suit a particular application. Cut-outs for the sanitary ware are undertaken on site, to allow for flexibility/tolerance. Additional cut-outs for other accessories are possible.

Infill Panels: The infills form an integral part of the framework, consisting of vertical infills, a head infill and skirting, creating required shadow gaps/clearances to the vertical edge of the panels and at the floor and ceiling. 17mm finished thickness consisting of 15mm moisture resistant MDF core and faced with wood veneer with balancing backing laminate. Alternatively, WBP plywood can be supplied as skirting to accept finishes by others, such as tiling/vinyl. When fitted prior to the finished ceiling, the head infill can sit above the level of the ceiling, with the ceiling then subsequently fitted to the face of the head infill. Alternatively, if the ceiling is fitted first, then the head infill can be scribed to the underside of the ceiling.

Fittings: Access panels are factory fitted to framework, using adjustable zinc alloy die cast hinges and fastened using zinc alloy die cast locating catches. Panel accessed using supplied injection moulded key.

Finishes:

Panels: 1mm wood veneer from our standard range.

Infills: 1mm wood veneer from our standard range.